


Screened, PVC- insulated, numbered, PVC- inner- and outer sheath

Product Description

Well-proven, reliable;Economic solution



Application range

- In power chains or moving machine parts
- Use in measuring, control and regulating circuits
- Power circuits for electrical equipment in automation engineering
- Assembly lines, production lines, in all kinds of machines
- Plant engineering

Benefits

- Well-proven, reliable
- Economic solution

Design

- Extra fine strands of plain copper wires (Class 6)
- Core insulation: PVC
- Cores twisted in layers in short lay lengths
- PVC inner sheath, grey
- tinned copper braid
- Nonwoven wrapping
- PVC outer sheath, grey (RAL 7001)

Approvals (Norm references)

- For travel distances up to 10 m.
- Usage in Power Chains: Please comply with the assembly guidelines Appendix T3

Product features

- Low adhesive surface
- Flame retardant according to IEC 60332-1-2
- In damp and wet rooms
- Designed for up to 5 million bending change cycles in the power chain
- Outdoor use only with UV protection and in accordance with the temperature range.

Cross-References

Accessories

SILVYN® CHAIN Cable protection and guiding systems

Technical Data

Core identification code

Black with white numbers acc. to VDE 0293

Based on

Core in accordance with VDE 0245/0281

Sheath in accordance with VDE 0245/0281

Specific insulation resistance

> 20 GOhm x cm

Conductor stranding

Extra fine wire in acc. to VDE 0295 Cl.6 / IEC

60228 Cl.6

Minimum bending radius

For flexible applications: 7.5 x outside diameter

Static: 4 x cable diameter

Rated voltage

300/500 V

Test voltage

4000 V

Protective conductor

G = with protective conductor GN/YE

X = without protective conductor

Range of temperature

Flexing: 0°C up to +70°C

Fixed installation: -40°C up to +80°C

Article List

Part number	Number of cores and mm ² per conductor	Outer diameter in mm	Copper index kg/km	Weight kg/km
0026200	2 X 0,5	6.9	33.0	74
0026201	3 G 0,5	7.3	39.0	84
0026202	4 G 0,5	7.9	46.0	98



0026203	5 G 0,5	8.4	54.0	110
0026204	7 G 0,5	9.8	70.0	143
0026205	12 G 0,5	11.3	100.0	201
0026206	18 G 0,5	13.4	153.0	287
0026207	25 G 0,5	15.9	202.0	394
0026208	30 G 0,5	16.5	228.0	432
0026219	2 X 0,75	7.3	39.0	85
0026220	3 G 0,75	7.8	48.0	99
0026221	4 G 0,75	8.4	59.0	116
0026222	5 G 0,75	9.0	69.0	133
0026223	7 G 0,75	10.7	90.0	178
0026224	12 G 0,75	12.4	129.0	253
0026226	18 G 0,75	14.9	205.0	368
0026227	25 G 0,75	17.4	271.0	496
0026229	30 G 0,75	18.0	320.0	549
0026230	2 X 1,0	7.7	46.0	97
0026231	3 G 1,0	8.2	57.0	114
0026232	4 G 1,0	8.9	70.0	134
0026233	5 G 1,0	9.8	81.0	159
0026234	7 G 1,0	11.4	110.0	207
0026235	12 G 1,0	13.4	182.0	314
0026238	18 G 1,0	16.1	254.0	443
0026239	25 G 1,0	18.8	365.0	612
0026240	26 G 1,0	18.8	374.0	625
0026241	34 G 1,0	21.5	463.0	787
0026242	41 G 1,0	23.2	542.0	918
0026243	50 G 1,0	25.3	640.0	1120
0026249	2 X 1,5	8.4	58.0	117
0026250	3 G 1,5	9.0	75.0	139
0026251	4 G 1,5	9.9	91.0	169
0026252	5 G 1,5	10.9	112.0	201
0026253	7 G 1,5	12.7	145.0	262
0026254	12 G 1,5	15.1	247.0	404
0026255	16 G 1,5	16.8	314.0	503
0026256	18 G 1,5	17.8	348.0	560
0026257	25 G 1,5	21.2	498.0	793
0026259	34 G 1,5	23.9	700.0	1005
0026270	3 G 2,5	10.8	119.0	207
0026271	4 G 2,5	11.8	161.0	247
0026272	5 G 2,5	13.2	194.0	307
0026273	7 G 2,5	15.8	262.0	418



0026281	4 G 4	13.7	238.0	360
0026282	5 G 4	15.3	280.0	436
0026283	4 G 6	16.1	318.0	514
0026285	4 G 10	20.2	521.0	824
0026287	4 G 16	23.6	780.0	1207

Footnote:

All product related values as shown are nominal values unless specified differently. Further values, e.g. tolerances we submit on request - if available and released for publication.

Copper price basis: EUR 150 / 100 kg; For utilization and definition of 'Metal price basis' and 'Metal index' see Appendix T17

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: Coil \leq 30 kg and \leq 250 m, otherwise drum

Please specify the desired packaging size (e.g. 1 x 500 m drum or 5 x 100 m coils)

Photographs are not to scale and do not represent detailed images of the respective products.