

Highly flexible application

Product Description

Cables can be used for PROFIBUS-DP as well as PROFIBUS-FMS and FIP;CL3 for installation on trays



Application range

- PROFIBUS® (in accordance with DIN 19245 and EN 50170, e.g. for SIEMENS SIMATIC® NET, also suitable for FIP - Factory Instrumentation Protocol).

Benefits

- Cables can be used for PROFIBUS-DP as well as PROFIBUS-FMS and FIP
- CL3 for installation on trays

Design

- Outer sheath: special PVC compound

Approvals (Norm references)

- with UL/CSA-Approbation (CMG, CL3, SUN RES, Oil Res I)
- Flame retardant according to CSA FT4 UL Vertical-Tray Flame Test
- Oil resistant according to UL OIL RES I

Product features

- FESTOON: for cable trolley (festoon)
- The stated bit rates allow the following cable lengths (maximum) according of PROFIBUS User Organisation of one bus segment (Type A cable, PROFIBUS-DP):
93.75 kbit/s = 1200 m
187.5 kbit/s = 1000 m
500 kbit/s = 400 m
1.5 Mbit/s = 200 m
12.0 Mbit/s = 100 m



Technical Data

Mutual capacitance

(800 Hz): max. 30 nF/km

Peak working voltage

600 V (not for power purpose)

Minimum bending radius

Flexing: 70 mm

fixed installation: single 30 mm

Test voltage

C/C: 2000 V

Range of temperature

Flexing: -5°C up to +70°C

Fixed installation: -40°C up to +80°C

Characteristic impedance

150 +/- 15 Ohm

Article List

Part number	Article designation	Number of pairs and conductor diameter in mm	Outer diameter in mm	Copper index kg/km	Weight kg/km
2170331	UNITRONIC® BUS PB Festoon	1 x 2 x 0,64	8.0	26.0	64

Footnote:

All product related values as shown are nominal values unless specified differently. Further values, e.g. tolerances we submit on request - if available and released for publication.

Copper price basis: EUR 150 / 100 kg; For utilization and definition of 'Metal price basis' and 'Metal index' see Appendix T17

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: Coil ≤ 30 kg and ≤ 250 m, otherwise drum

Please specify the desired packaging size (e.g. 1 x 500 m drum or 5 x 100 m coils)

SIMATIC® is a registered trademark of SIEMENS AG. FIP is a registered trademark of World FIP

Lapp Kabel is a member of the PROFIBUS user organisation (PNO)

Photographs are not to scale and do not represent detailed images of the respective products.